

A139

LOGISTIC VINYL

Description

A139 Logistic Vinyl is suitable for a wide variety of indoor and medium-term outdoor applications, such as general purpose signage, decorative panels, directional signage, medium-life outdoor advertising, point-of-sale displays, fleet marking, public transport advertising, etc. The specially-formulated, flexible films can be cut easily and weeded quickly. A permanent, solvent-based adhesive creates a strong final bond to ensure a secure and durable finish. The inherent properties of the products promote excellent cutting and weeding characteristics because of the high-quality, PE-coated, silicone liner. For white vinyl, a light blue silicone liner is used to form a stronger contrast to lettering. A139 Logistic Vinyl with a gloss finish is also suitable for thermal transfer printing (with resin ribbons).

Material	Vinyl
Finishing	Glossy
Color	White / Yellow
Adhesive	Solvent based acrylic, permanent
Adhesive strength	20N/25mm (Finat TM 1/24h)
Liner	PE-coated silicone liner, 140g/m ² , white vinyl with blue contrast liner

Temperature range	-30°C to +90°C
Thickness	75µ
Flame retardancy	B1
Shelf life	2 years, 20°C / 50% humidity
Durability	4 years

Certificates

REACH

Please contact Altec for the latest REACH document available.

RoHS

Please contact Altec for the latest RoHS document available.

Disclaimer:

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.