

A325

CLING POLYOLEFIN

Description

A325 80 micron matt white print receptive Yupo polyolefin offers good chemical, humidity and abrasion resistance. Designed to accept conventional inks and variable information via thermal transfer. A325 is coated with "cling" adhesive which exhibits excellent permanent adhesion when applied to itself. Also suitable for application to glass where clean removability and repositionability is required.

Facestock	80 micron matt white print receptive polyolefin offers very good chemical, humidity and abrasion resistance. Designed to accept conventional inks, thermal transfer and is pen writable.
Adhesive	Repositionable "cling" adhesive is a proprietary coating offering excellent adhesion and cohesive strength when applied to itself for back-to-back loop labels. Once applied the product is initially removable, ultimate adhesion is reached after 72 hours. Warning: should not be applied to PVC or polycarbonate substrates.
Liner	40 micron polypropylene
Color	White
Finishing	Matt

Physical data

Properties	Typical values		Unit of measure	Test method
Physical	Facestock Adhesive Liner		80μ ± 10% 20gsm ± 10% 40μ ± 10%	FTM 12
Peel adhesion	Initial	24 hours	N/25mm @ 23°C, 50% RH	FTM1
Stainless steel	N/A	0.4		
Glass	N/A	0.7		
Polycarbonate	N/A	12.8		
PVC	N/A	15.5		
Chemical resistance	3.0 – Good		Grey scale 1 = poor / 5 = superior	AATCC 8
Min. application temperature	+10°C		Celcius	
Service temperature range	-30°C to +60°C		Celcius	
Outdoor durability	Not recommended for prolonged outdoor exposure		No reference	

Certificates

REACH

Please contact Altec for the latest REACH document available.

RoHS

Please contact Altec for the latest RoHS document available.

Disclaimer

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.