

A393

ULTRA REMOVABLE PAPER

Description

Facestock	Coated paper
Adhesive	Acrylic type adhesive
Release liner	Glassine paper (blue)

Physical data

Item	Value	Test method
Thickness	Facestock (µm)	77
	Liner (µm)	67
Basis weight	Facestock (g/m ²)	82,5
Adhesion	After 30 min. (N/25mm)	1.0
	After 24 hrs. (N/25mm)	1.0
Holding power	(Sec.)	< 100
Adhesion	JIS method (N/10mm)	0.2
Ball Tack	(No.)	6
		Altec method
		JIS Z 0237
		J. Dow method

Storage

- Avoid storage in places with high humidity and high temperature, and low temperature.
(Ideally store Temperature: 10°C~30°C, Humidity: less than 70%RH)
- At extreme condition, the adhesion and/or holding strength may deteriorate and become easier to peel off.
- Contact with water or chemical must be avoided, so polyethylene film packaging is recommended.
- Direct exposure to the sunlight must be avoided and a distance must be kept from the light source.
- To ensure a longer shelf life, store the rolls in a standing position and sheets in laying position and avoid causing any form of impact on the material.

Application / Features

- Reapplicable type adhesive
- Ability to attach and remove repeatedly
- Able to remove without damaging the applied surface
- Convenient for corrective label with writable surface

Disclaimer

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.