

AWH-20

INK RIBBON



Product description

This grade is one of the best performing at head technology wax resin grades on the market and offers an excellent all round high performance for printing dark, crisp images and barcodes on a wide range of paper and synthetic labels, with the durability and smudge/scratch resistance expected of such a premium product. Developed specifically to cover the widest possible range of synthetic materials and coated papers, this grade offers the highest level of durability and performance from a at head technology wax resin grade. This grade has been developed to print at low energy levels allowing for higher print speeds. It has also been used very successfully as a replacement grade for the world's leading wax resin grade, Ricoh B110A.

Reconnended substrates

Coated/uncoated paper & tag stocks, synthetic paper, polyethylene, polypropylene, polyole-n, gloss paper, ood-coated paper, UV varnished labels

Performance properties

PRINT SENSITIVITY

9

HEAT RESISTANCE

8

ABRASION RESISTANCE

9

SOLVENT RESISTANCE

6

LABEL ADAPTABILITY

9

Low

Medium

High

Performance characteristics

- High levels of print durability
- Prints on a wide variety of substrates from uncoated papers to mid-range synthetic -lms
- Dark, dense images for reliable printing
- Prints at high speeds delivering crisp, rotated barcodes
- Dissipates static
- Heat resistant up to 120°C on certain materials
- Features enhanced printer performance
- Meets BS5609 standards with certain label materials
- Excellent replacement grade for Ricoh B110A

| Ribbon specifications | |
|------------------------|-----------------------------------|
| Description | Technical |
| BASE FILM CARRIER | 4.5 Micron Polyester |
| TOTAL RIBBON THICKNESS | 6.8 Microns +/- 0.02 |
| INK TYPE | Wax/Resin (at head technology) |
| COLOUR | Black |
| INK MELTING POINT | 75°C |
| DENSITY | 1.8 |

| Ribbon storage conditions | |
|---------------------------|------------------------------|
| Description | Technical |
| TEMPERATURE | 5°C to 35°C (41F to 95F) |
| HUMIDITY | 10% to 85% relative humidity |
| LIGHT | Avoid direct sunlight |

| Certifications and approvals | |
|--------------------------------|---|
| Description | Technical |
| ISO 9001:2015 & ISO 14001:2015 | All ribbons have been manufactured to these international quality standard |
| RoHs/WEEE | EC directives 2012/19/EU and 2011/65/EU, compliance to the limitation of dangerous substances in electrical and electronics equipment |
| HEAVY METALS | 94/62/EC & 2011/65/EU |
| TSCA/CP 65 | The ribbon does not contain any of the substances on this list |
| AMES TEST | The ribbon is not mutagenic, does not cause DNA modifications |
| EC DIRECTIVES | 1999/45/EC and 2001/59/EC. This ribbon does not contain any substance classified as dangerous for health |
| FOOD CONTACT | 1935/2004/EC |
| REACH/SVHC | Does not contain any of the SVHCs listed - 1907 / 2006/EC |
| DISPOSAL | To be disposed of as mixed industrial waste |

Disclaimer

Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available as is and that Altec gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.